

CENTER CUL-DE-

HOT MIX ASPHALT-

GRAVEL BASE

CRUSHED SURFACING TOP COURSE

NOTES:

 LENGTH MEASURED ALONG CENTER LINE: MINIMUM = 100 FEET MAXIMUM = 400 FEET

2. STANDARD MONUMENT TO BE INSTALLED AT BOTH THE CENTER OF THE CUL—DE—SAC AND AT THE OFFSET POINT ON THE CENTERLINE OF THE STEM. SEE STANDARD DRAWING DM.F1.1.

- 3. MAXIMUM OFFSET:X = 40-Y/2 LANDSCAPED CENTER ISLAND MAY BE PROVIDED.
- 4. MAXIMUM RADIUS OF ISLAND IS 10'. ISLAND SHALL HAVE CENMENT CONCRETE TRAFFIC CURB.

TYPICAL SECTION A-A

1.5% SIDEWALK

CRUSHED SURFACING TOP COURSE

CURB AND GUTTER

REFER TO STANDARD DRAWING DM.A5.1 FOR PAVEMENT SECTION DETAILS.

NOT TO SCALE



CITY OF DES MOINES
PUBLIC WORKS DEPARTMENT
ENGINEERING SERVICES
21650 11TH AVENUE SOUTH
DES MOINES, WA 98198
SAILS WITH PRIDE