



BICYCLE DETECTOR SYMBOL

PAVEMENT MARKING DETAIL

BICYCLE LANE SYMBOL LAYOUT

BICYCLE DETECTOR PAVEMENT MARKING DETAIL

NOTES:

1. ALL BICYCLE PAVEMENT MARKINGS FOR BICYCLES SHALL BE LOW PROFILE PRE-FORMED TYPE B HEAT FUSED THERMOPLASTIC (90 MILS.),
2. BICYCLE LANE MARKINGS SHALL BE USED IN CONJUNCTION WITH BICYCLE LANE SIGNAGE.
3. BICYCLE LANE SIGNS (R3-17) SHALL BE USED IN ADVANCE OF THE BEGINNING OF A MARKED BICYCLE LANE. SEE STANDARD DRAWING DM.F5.1 - DM.F5.3.
4. BID ITEM "BICYCLE LANE SYMBOL" INCLUDES BIKE LANE ARROW AND BIKE RIDER SYMBOL.
5. SEE WSDOT STANDARD PLANS FOR LOOP DETECTOR DETAILS.
6. ALL CHANNELIZATION (OR PAVEMENT MARKINGS) SHALL BE LAID OUT WITH SPRAY PAINT AND APPROVED BEFORE FINAL INSTALLATION. APPROVALS SHALL REQUIRE ADVANCE NOTICE OF THREE WORKING DAYS TO HAVE FIELD LAYOUT APPROVED.

NOT TO SCALE



**CITY OF DES MOINES
PUBLIC WORKS DEPARTMENT**

ENGINEERING SERVICES
21650 11TH AVENUE SOUTH
DES MOINES, IA 50319



BICYCLE LANE MARKINGS

DM.F2.3

REVISED: 02/23